


SG SERIES

Gas Tilting Mixing Kettle



MODELS

- Swirl Wok 100
- Swirl Wok 250

TECHNICAL SPECIFICATIONS

- Free-standing tilting SS304 ceramic wool insulated kettle with Polished SS304 **6mm** 250-litre capacity wok-type dish.
- Polished SS304 frame with panels, castor wheels and level pads.
- SS304 Lid
- 1.4 lakh BTU Burner kit with automatic pilot ignition and flame failure cut-off device.
- Ss control and operation panel.
- 1.5 HP high torque (296Nm) mixing motor housed in powder coated rigid transmission case.
- Variable speed mixing assembly with removable Teflon liners for.
- Solid state controls with water-tight enclosure and push buttons.

STANDARD FEATURES

- **6mm SS304** cooking surface.
- **Full SS304 frame and kettle** with adjustable flanged feet.
- Formed pouring lip for easy unloading of material.
- **VFD** controlled stirrer for smooth mixing
- **IP55 sealed oil filled high-torque motor** with long service life
- Manually operated **anti-jam tilting mechanism** with removable handle; kettle can be **fully tilted** to empty completely.
- Rapid heating with **1.40 lakh BTU burner**
- Solid state ignition controller with **automatic emergency flame shut-off controls** offers full operator safety.
- Easily **accessible gas regulator**.
- Watertight controls and enclosures
- **Two-year** limited parts and labour warranty
- **One-touch tilt lock** mechanism enables

FACTORY-INSTALLED OPTIONS

- Motor driven kettle tilting with removable manual crank handle (in-case of unexpected power failure)
- Third year extended limited parts and labour warranty
- SS316 cooking surface and liner available on request

ACCESSORIES

(PACKAGED AND SOLD SEPARATELY)

- Set of four casters, (two locking)
- Washdown hose with backflow preventer
- Pantry hose with backflow preventer
- Optional removable SS perforated strainer
- Check valve and LPG regulator

INSTALLATION INSTRUCTIONS

- Electrical connection with 3-phase 440 V
- Water connections for filling and washdown faucets
- LPG line with check valve and regulator




STORM

SG SERIES

Gas Tilting Mixing Kettle

DRAWING VIEWS



CONFIGURATIONS

MODEL	DIMENSIONS [L x H x D] (in)	CAPACITY (working)	INLET PRESSURE	ELECTRICAL LOAD	WEIGHT
SW100	60 x 64 x 37	100 liters	2.5psi LPG	0.75 kW / 1 HP	200 kg
SW250	66 x 68 x 47	250 liters	2.5psi LPG	1.33 kW / 1.5 HP	510 kg